



CODE NO.	dim	DN	PN	L	H	lg	øA	SW	WEIGHT/G
615 50015	1/2"	12	25	56	33	11	25	28	220
615 50020	3/4"	15	25	67	38	12	30	34	330
615 50025	1"	18	25	78	42	14	35	41	530
615 50032	1-1/4"	26	25	90	50	15.5	44	51	880
615 50040	1-1/2"	30	25	103	57	16	53	57	1200
615 50050	2"	40	25	120	65	18	62	70	2000

NO.	PARTS	MATERIAL
1	BODY	BRONZE
2	BONNET	BRONZE
3	SEAL CLAW	BRONZE

Specification:

- 1.Nominal pressure : 2.5MPA
2. Working medium: sea water, oil, liquefied gas, steam
3. Working Temperature: water below 120 °C , oil gas, steam below 220 °C
4. Thread standard: according to ISO228-1;

REMARK:

- 1.THE UNIT WEIGHT CAN BE ACCEPTED WITH IN ±3%.
- 2.THE TOLERANCE CAN BE ACETED AS FOLLOWING SHEET.

TOLERANCES	LINEAR-DIMENSION					DESIGNED & PRODUCED BY:
	>6-30	>30-60	>60-120	>120-200	>200-300	
ALL DIMENSIONS IN	±0.2	±0.3	±0.7	±1	±3	DAWOO VALVE
						DRAWING NO.: SLZHR61550015-050
						玉环县大通阀门有限公司 YUHUAN DAWOO VALVE CO., LTD 受控文件 CONTROLLED DOCUMENTS (2015)
						BRONZE LIFT CHECK VALVE
						15MM-50MM
						DATED:DEC. 7TH, 2015